


Marlow®

DATASHEET

MARLOWBRAID



CONSTRUCTION

MATERIAL CORE: High Tenacity Polyester
MATERIAL COVER: High Tenacity Polyester
CORE CONSTRUCTION: Long lay 3 Strand
COVER CONSTRUCTION: 16 Plait Braided

PROPERTIES

LOW STRETCH
HIGH STRENGTH: Good general purpose line
GOOD UV RESISTANCE: Durable

PERFORMANCE

DIAMETER		CIRCUMFERENCE		MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN		
6	7/32	27	2.01	986	1982	8.8	829	1824	8.1		
8	5/16	45	3.02	1577	3828	17.1	1601	3522	15.7		
9	3/8	55	3.69	2270	4994	22.3	1990	4378	19.5		
10	13/32	73	4.90	2850	6270	28.0	2622	5768	25.7		
12	1/2	100	6.71	4450	9790	43.7	4094	9007	40.2		
14	9/16	145	9.72	5460	12012	53.6	5023	11051	49.3		
16	5/8	190	12.74	7420	16324	72.8	6650	14630	65.2		
18	3/4	235	15.76	10190	22418	100.0	9375	20625	92.0		
20	13/16	285	19.11	11340	24948	111.2	10433	22952	102.3		
24	15/16	420	28.17	14000	30800	137.3	12600	27720	123.6		

Marlow Ropes Ltd
 Ropemaker Park
 Hailsham
 East Sussex, BN27 3GU
 England

Marlow Ropes, Inc.
 Cordage Business Park
 Plymouth
 MA 02360
 USA

www.marlowropes.com
 UK: +44 (0) 1323 444 444
 sales@marlowropes.com
 US: +1 508 830 444
 salesusa@marlowropes.com



Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.