CUSTOME	RDATASHEET Printed: 23/01/2017 Product Management Transportation Europe
Central Article Code: D04070A18-A Local Code:	Created: 08/06/2010 Modified: 18/06/2015
	Final Outlook D0418-A Approval date 15/06/2010
PERFORMANCES	CONTAINER
Voltage (V): 12 V C20 (Ah): 140.0 20 h Cranking (A): 700 EN	Type: D04 BLACK Hold Down: B0 H.D. Adapter: No
Charge: CHARGED	COVER
Technology: AGM	Type: Double without BLUE LIGHT
Grid: Ca/Ca	Polarity: ETN 3
Vibration: V1 (35Hz/3g/2h)	Terminals: EN taper post
Endurance: 300 cycles@75%	Terminal Adapter:NoSOCI:NoVentilation:CentralFilter:1 FilterLateral Plug:No
STD. DIMENSIONS	DILICE
	PLUGS
Length (mm ± 2): 513	Type: 1 x Valve+Cov BLUE LIGHT
Length (mm ± 2): 513 Width (mm ± 2): 189 Height (mm ± 2): 223	
Length (mm ± 2): 513 Width (mm ± 2): 189 Height (mm ± 2): 223	Type: 1 x Valve+Cov BLUE LIGHT
Length (mm ± 2): 513 Width (mm ± 2): 189 Height (mm ± 2): 223	Type: 1 x Valve+Cov BLUE LIGHT HANDLES
Length (mm ± 2): 513 Width (mm ± 2): 189 Height (mm ± 2): 223	Type: 1 x Valve+Cov BLUE LIGHT HANDLES Type: 2 x Rope (Rigid holde BLACK
Length (mm ± 2): 513 Width (mm ± 2): 189 Height (mm ± 2): 223	Type: 1 x Valve+Cov BLUE LIGHT HANDLES Type: 2 x Rope (Rigid holde BLACK OTHERS

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.