



GASOLINE FUME DETECTOR WITH TWO PLASTIC SENSORS

G-2B-R



Detect gasoline leaks early to
prevent personal injury and
possible explosions.

ON BOARD, ON GUARD!

PACKAGE CONTENTS:

Gasoline Detector	G2BS-N01-D
(2) Plastic Fuel Sensors	FS-T01-S
(2) Extension Cables, 20 ft. (6 m)	FS-X01 CABLE 20'
Manual	18140

INSTALLATION:

- 1 Drill a 2-1/8 in. (54 mm) round hole
- 2 Install helm display through the hole and secure with threaded mounting nut
- 3 Mount sensors & Plug in extension cables
- 4 Connect power and ground wires to a 9-30 VDC source

FEATURES / SPECIFICATIONS:

- ▶ Xintex Detector with (2) Gasoline Sensors
- ▶ Operating Temperature: -40° F to 185° F (-40° C to 85° C)
- ▶ 2-5/8 in. (67 mm) Square Display with LEDs & Silence/Test Button
- ▶ Reverse Polarity Protected
- ▶ 68 dBA Alarm will Sound and Red LED will light at 20% of the LEL
- ▶ Current Draw @ 12 VDC:
 - Nominal: 95 mA
 - Maximum: 150 mA
- ▶ Simple Installation
- ▶ 9-30 VDC

Fireboy-Xintex, a global supplier of safety products, provides a variety of reliable **fire detection** and **fire suppression** products in addition to **gas detection and control systems**.

Pre-engineered and custom engineered fire suppression systems are available.



MADE IN THE USA

SAFETY

FIREBOY® - XINTEX®

XINTEX



(616) 735-9380 fireboy-xintex.com

O-379 Lake Michigan Dr NW / Grand Rapids, MI 49534