

Easy Access and Product Protection

- Meets requirement for primary bilge pump for boats up to 12 m (39.4 ft) length
- Ideal where bilge space is limited
- Long life high, dry and protected

3 Year Warranty

Awards and Accreditations

- ISO15083 Marine standard suitable as a primary bilge pump (for vessels up to 12m in length) or secondary bilge pump in accordance with ISO8849.
- Ignition protection ISO8846.
- CE marked.

COMPLETE YOUR SYSTEM

See page 40 - 43 for bilge accessories

YOU MAY ALSO LIKE

Bilge IC - Pre-wired Automatic Bilge System with Intelligent Control - page 16

Supersub Smart - Narrow low profile Automatic Electric Bilge Pumps with Intelligent Control - page 12



Product Information

Model Specifications

| Model | Gulper® 320 | |
|--|---|---------------------------------|
| Product Code (retail) | BP2052 (includes 3/4" strainer) | BP2054 (includes 3/4" strainer) |
| Voltage | 12 V d.c. | 24 V d.c. |
| Hose Connections | 3/4" (19 mm) + 1" (25 mm) | |
| Recommended Fuse Size | 10 amp Automotive | 5 amp Automotive |
| Minimum Wire Size | 1.5 mm ² (16 AWG) | |
| Weight | 1.6 kg (3.5 lbs) | |
| Materials | Pump Head: Glass-filled Nylon, Valves and Diaphragm: Santoprene® | |
| Accessories | SB3422 (19 mm) strainer (multi-directional port) Service Kit: AK2050 - replacement pump head | |
| Maximum Suction Lift | 3 m (10 ft) | |
| Maximum Discharge Head | 3 m (10 ft) | |
| Maximum Discharge Head and Suction Lift Combined | 4 m (13.5 ft) | |

Performance Data

| Product Code | BP2052 / BP2054 | | | |
|----------------------|---|--|---|--|
| Suction Lift | 0 m | 0 m | 1 m (3 ft) | 1 m (3 ft) |
| Discharge Head | 1 m (3 ft) | 1 m (3 ft) | 1m (3 ft) | 1 m (3 ft) |
| Hose Size | 3/4" (19 mm) | 1" (25 mm) | 3/4" (19 mm) | 1" (25 mm) |
| Flow Rate per Minute | 19 ltrs (5 US Gals) | 17.5 ltrs (4.6 US Gals) | 17.4 ltrs (4.5 US Gals) | 15.5 ltrs (4.1 US Gals) |
| Current Draw | 7.5 amps (12 V d.c.) 3.25 amps (24 V d.c.) | 8 amps (12 V d.c.) 4 amps (24 V d.c.) | 7.5 amps (12 V d.c.) 3.25 amps (24 V d.c.) | 8 amps (12 V d.c.) 4 amps (24 V d.c.) |

Note: These specifications are retail items only.

For details of our bulk pack range for boat builders and wholesalers - contact Whale Support.

EASY ACCESS FOR INSPECTION

